




Cemented Carbide Standard Bolts Reducing Dies



Unit: mm

Type	d	D	L	d1	apply to
CTC-SΦ2.1×Φ14×15	2.1	14	15	2.5	M3
CTC-SΦ2.1×Φ14×30			30		
CTC-SΦ2.1×Φ16×30			30		
CTC-SΦ3.1×Φ14×15	3.1	14	15	3.5	M4
CTC-SΦ3.1×Φ14×30			30		
CTC-SΦ3.1×Φ16×15		16	15		
CTC-SΦ3.1×Φ16×30			30		
CTC-SΦ3.9×Φ14×15	3.9	14	15	4.5	M5
CTC-SΦ3.9×Φ14×20			20		
CTC-SΦ3.9×Φ14×35			35		
CTC-SΦ3.9×Φ16×15		16	15		
CTC-SΦ3.9×Φ16×20			20		
CTC-SΦ3.9×Φ16×35			35		
CTC-SΦ4.7×Φ16×15	4.7	16	15	5.4	M6
CTC-SΦ4.7×Φ16×35			35		
CTC-SΦ4.7×Φ18×20		18	20		
CTC-SΦ4.7×Φ18×35			35		
CTC-SΦ6.5×Φ20×20	6.5	20	20	7.2	M8
CTC-SΦ6.5×Φ20×42			42		
CTC-SΦ6.5×Φ22×20		22	20		
CTC-SΦ6.5×Φ22×42			42		
CTC-SΦ8.4×Φ2.6×25	8.4	2.6	25	9.3	M10
CTC-SΦ8.4×Φ2.6×54			54		
CTC-SΦ8.4×Φ30×25		30	25		
CTC-SΦ8.4×Φ30×40			40		
CTC-SΦ8.4×Φ30×54			54		
CTC-SΦ10.2×Φ28×26	10.2	28	26	11.4	M12
CTC-SΦ10.2×Φ28×54			54		
CTC-SΦ10.2×Φ30×25		30	25		
CTC-SΦ10.2×Φ30×54			54		



Continued

Unit: mm

Type	d	D	L	d1	apply to
CTC-SΦ11.9×Φ40×30	11.9	40	30	13.2	M14
CTC-SΦ11.9×Φ40×40			40		
CTC-SΦ14×Φ40×30	14		30	15.4	M16
CTC-SΦ14×Φ40×35			35		
CTC-SΦ14×Φ40×40		40			
CTC-SΦ17.5×Φ45×30	17.5	45	30	19.3	M20
CTC-SΦ17.5×Φ45×40			40		
CTC-SΦ17.5×Φ45×50			50		
CTC-SΦ17.5×Φ45×54			54		

Tolerance: d: -1.1~0; L、D: +0.5~+2.5; curvature: ≤0.55