


Cemented Carbide Spherical Button-Type CQ



Unit: mm

Type	D	H	R	h	β°	e
CTC-GCQ-0810	8.0	10.0	4.6	7.5	18°	1.2
CTC-GCQ-0911	9.0	11.0	4.0	6.5	18°	1.2
CTC-GCX-99518	9.7	14.2	5.1	10.7	16°30'	1.5
CTC-GCX-99521	10.1	15.0	5.5	11.6	16°	1.4
CTC-GCQ1214A	12.0	14.0	6.7	10.1	18°	1.5
CTC-GCX-99524	12.0	19.0	6.6	15.0	16°	2.0
CTC-GCX-98505	13.8	22.5	7.0	16.0	16°	1.5
CTC-GCX-99515	14.0	22.0	7.4	17.0	15°	1.5
CTC-GCX-99519	15.9	21.0	8.0	14.1	15°	1.8
CTC-GCQ-1622	16.0	22.0	8.0	14.0	18°	1.8
CTC-GCQ-1623	16.0	23.0	8.3	17.0	18°	1.8
CTC-GCX-98504	16.8	21.5	8.5	13.5	16°	1.8
CTC-GCX-99516	19.0	28.0	10.3	21.5	15°	2.5
CTC-GCQ-2030	20.0	30.3	10.0	20.0	18°	2.0

Tolerance: D: +0.05; H: ±0.30